






HEATING CABLE ACCESSORIES

Catalog Number	Description
GLT-16m 	16.5m (54 ft) roll of glass tape used for attaching SR heating cable to pipes. For installations ranging between -40°C (-40°F) up to 500°C (932°F). Glass tape rolls have a width of 12mm (0.5 inches). For use on all pipe types.
ALT-55m 	55m (180 ft) roll of aluminum tape used for attaching heating cables and RTD's to pipes, tanks and motors where glass tape is unable to be used. Minimum recommended installation temperature is 0°C (32°F). The aluminum core provides excellent heat transfer and spreads heat efficiently. Aluminum tape rolls have a width of 64mm (2.5 inches). For use on all pipe types.
SSPS-01 SSPS-02 SSPS-10 SSPS-20 	Stainless Steel pipe straps are available in multiple sizes for any installation requirement. Pipe straps are screw tightened. The sizes range from installs on less than 1 inch pipes up to 20 inch pipes. Orders should be based off of the pipe size. SSPS-01—Pipe Straps for pipes with a diameter of less than 1 inch SSPS-02—Pipe Straps for pipes with a diameter of less than 2 inches SSPS-10—Pipe Straps for pipes with a diameter greater than 2 inches but less than 10 inches SSPS-20—Pipe Straps for pipes with a diameter greater than 10 inches but less than 20 inches
JBSR-SPA 	Small pipe adaptor for mounting JBSR-S, JBSR-M, and EKSr-HP to pipes with a diameter of 1 inch or less.

Catalog Number


Description

MB-300



304 Stainless steel mounting bracket, 305mm, (12 inches) for JBMI fiberglass enclosures. Brackets are to be installed on the pipe prior to the insulation being installed. Two brackets are required for each enclosure.

MB-400



304 Stainless steel mounting bracket, 406mm, (16 inches) for JBMI fiberglass enclosures. Brackets are to be installed on the pipe prior to the insulation being installed. Two brackets are required for each enclosure.

TW-16



16 Gauge tie wire used for securing Mineral Insulated (MI) heating cables to pipes, tanks and motors.

EHT-L



Heat trace label identifying which pipes and tanks are Electrically Heat Traced. Labels are available in two sizes, 255mm x 127mm (10 inches x 5 inches) and 150mm x 76mm (6 inches x 3 inches). The smaller labels are recommended for areas where the larger labels will not fit. The larger labels are recommended for all other applications.